CLAIMS:

5

10

15

- 1. A speaker cabinet composed of a mixture of a non-chlorinated resin and a cellulose powder, wherein the powder consists of particles whose diameters are included in a range from about $5 \mu m$ to $500 \mu m$.
- 2. A speaker cabinet as defined in claim 1, wherein content by weight of the cellulose powder in the mixture is from about 30 % to 70 %.
- 3. A speaker cabinet as defined in claim 1 or 2, wherein the resin is selected from the group consisting of polyolefin resins, polyester resins and polystyrene resins.
- 4. A speaker cabinet as defined in claim 1, 2 or 3, wherein the cellulose powder is surface-treated to increase affinity for the non-chlorinated resin.
- 5. A speaker cabinet as defined in any one of the preceding claims 1 to 4, wherein the mixture is colored with a colorant.
 - 6. A speaker cabinet as defined in claim 1, 2 or 4, wherein the cellulose powder has an intrinsic perfume, and the mixture is molded at a temperature within a range from 160 °C to 200 °C.
- 7. A speaker cabinet as defined in any one of the preceding claims 1 to 6, wherein the cellulose powder is surface-esterified using a polybasic acid anhydride so as to increase affinity for the non-chlorinated resin.
- 8. A speaker cabinet as defined in any one of the preceding claims 1 to 7, the mixture of the non-chlorinated resin and a esterified cellulose powder further comprises an organic peroxide.

25

20